

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows.

1. (Currently Amended) Δ [[W]]windscreen wiper system for motor vehicles, comprising:
~~particularly for motor vehicles with~~
 at least three connections at intervals from one another for screw-free installation of [[a]]
the windscreen wiper system or a carrier of the[[is]] windscreen wiper system on
a vehicle bodywork, wherein each of the at least three connections comprise
fixing elements integrally moulded on windscreen wiper system or carrier, the
fixing elements comprising:
~~with the fixings consisting respectively of a first fixing element which can~~
configured to be pushed into an attachment or fixing hole, wherein the
first fixing element is it can be anchored by engagement, and [[with]]
 at least one second fixing element having a grommet in elastic material which ~~can~~
be is inserted into the attachment or fixing hole, ~~designed with~~
wherein the grommet comprises:
 at least one projection acting as a catch, ~~characterised by the fact, that~~
wherein, on the grommet in [[the]] an area of the at least one
projection, at least one cavity is arranged radially inwards opposite
the at least one projection with reference to a grommet axis,
wherein the grommet is arranged secured against axial displacement on a peg or a
peg section of the at least one second fixing element, safeguarded by back
cuts between the peg and the grommet axially on the peg, and wherein the
peg or the peg section has at least one groove to accept the grommet.
2. (Currently Amended) The [[W]]windscreen wiper system according to claim 1, wherein
~~characterised by the fact that the cavity is a cutout, for example a circular groove-~~
[[like]]shaped cutout.
3. (Currently Amended) The [[W]]windscreen wiper system according to claim 2, characterised
~~by the fact that~~wherein the cavity is a cutout open towards [[the]] a circumference of the
grommet.

4. (Currently Amended) The ~~[[W]]~~windscreen wiper system according to claim 1, wherein ~~characterised by the fact that~~ the cavity has an extension stretching under the at least one projection.
5. (Currently Amended) The ~~[[W]]~~windscreen wiper system according to claim 1, wherein ~~characterised by the fact that~~ the cavity on ~~[[the]]~~ a circumferential area of the grommet is open near ~~[[the]]~~ a locking area, wherein the locking area is formed by a side of the at least one projection that is facing a flange-shaped section of the grommet.
6. (Currently Amended) The ~~[[W]]~~windscreen wiper system according to claim 1, ~~characterised by the fact that~~ wherein the at least one projection is a circular-shaped projection concentrically enclosing the grommet axis.
7. (Withdrawn) The ~~[[W]]~~windscreen wiper system according to claim 1, wherein ~~characterised by the fact that~~ the cavity is formed by a section of the grommet opening with an enlarged cross-section.
8. (Currently Amended) The ~~[[W]]~~windscreen wiper system according to claim 1, ~~characterised by the fact that~~ wherein the grommet is manufactured from ~~an elastic rubber material, for example from rubber or an elastic rubber plastic.~~
9. (Currently Amended) The ~~[[W]]~~windscreen wiper system according to claim ~~[[1]]~~ 5, wherein ~~characterised by the fact that~~ the grommet forms a further contact surface axially distanced from the ~~at least one~~ locking area, and ~~[[that]]~~ wherein an ~~[[the]]~~ axial distance between the~~[[se]]~~ further contact surface~~[[s]]~~ on the grommet side and the ~~at least one~~ locking area are ~~at the most~~ equal to or less than ~~[[the]]~~ an axial distance between a first surface gripped from behind at the attachment or fixing hole formed by the locking area and a second surface formed at the attachment or fixing hole which lies against the further contact surface on the grommet side.
10. (Currently Amended) The ~~[[W]]~~windscreen wiper system according to claim 9, wherein ~~characterised by the fact that~~ the further contact surface on the grommet side is formed by a flange-~~[[like]]~~shaped grommet section projecting over ~~[[the]]~~ a circumference of the grommet.

11. – 13. (Cancelled)

14. (Currently Amended) The [[W]]windscreen wiper system according to claim 1, wherein characterised by the fact that the first and at least one second fixing elements are at least arranged in part on the windscreen wiper system or on an element of the windscreen wiper system and the corresponding fixing or attachment openings are arranged on the bodywork side.
15. (Currently Amended) The [[W]]windscreen wiper system according to claim 1, wherein characterised by the fact that the first and at least one second fixing elements are at least arranged in part on [[the]] a bodywork side of the vehicle and the corresponding fixing or attachment openings are arranged on the windscreen wiper system or on a functional element of the windscreen wiper system.
16. (Currently Amended) The [[W]]windscreen wiper system according to claim 1, wherein characterised by the fact that the a volume of the at least one cavity is at least equal to [[the]] a volume of the at least one projection.
17. (Currently Amended) A [[F]]fixing element for screw-free installation of a windscreen wiper system for motor vehicles, ~~particularly for motor vehicles~~ on vehicle bodywork, wherein:
in which the fixing element ~~which can~~ is configured to be pushed into an attachment or fixing hole and to be anchored there by engagement, the fixing element comprising [[has]] a grommet made of an elastic material, which ~~can be~~ is inserted into the attachment or fixing hole, wherein the grommet comprises ~~and is designed for engagement with~~ at least one projection acting as a catch with which the grommet engages in the attachment or fixing hole,
wherein, characterised by the fact, that on the grommet in the area of the at least one projection, at least one cavity is arranged radially inwards opposite the at least one projection with reference to a grommet axis.
18. (Currently Amended) The [[F]]fixing element according to claim 17, wherein characterised by the fact that the cavity is a cutout, ~~for example a circular groove~~ [[like]]shaped cutout.

19. (Currently Amended) The ~~[[F]]~~fixing element according to claim 18, ~~wherein~~characterised by the fact that the cavity is a cutout open towards the circumference of the grommet.
20. (Currently Amended) The ~~[[F]]~~fixing element according to claim 17, characterised by the fact that wherein the cavity has an extension stretching under the at least one projection.
21. (Currently Amended) The ~~[[F]]~~fixing element according to claim 17, ~~wherein~~ characterised by the fact that the cavity, on ~~[[the]]~~ a circumferential area of the grommet, is open near ~~[[the]]~~ a locking area, wherein the locking area is formed by a side of the at least one projection that is facing a flange-shaped section of the grommet.
22. (Currently Amended) The ~~[[F]]~~fixing element according to claim 17, characterised by the fact that wherein the at least one projection is a circular-shaped projection concentrically enclosing the grommet axis.
23. (Withdrawn) Fixing element according to claim 17, characterised by the fact that the cavity is formed by a section of the grommet opening with an enlarged cross-section.
24. (Currently Amended) The ~~[[F]]~~fixing element according to claim 17, ~~characterised by the fact that wherein~~ the grommet is manufactured from ~~an elastic rubber material, for example from rubber or an elastic rubber plastic.~~
25. (Currently Amended) The ~~[[F]]~~fixing element according to claim ~~[[17]]~~ 21, wherein characterised by the fact that the grommet forms a further contact surface axially distanced from the at least one locking area and that the axial distance between the~~[[se]]~~ further contact surface~~[[s]]~~ on the grommet side and the at least one locking area are at the most equal to or less than the axial distance between a first surface gripped from behind at the attachment or fixing hole formed by the locking area and a second surface formed at the attachment or fixing hole which lies against the further contact surface on the grommet side.
26. (Currently Amended) The ~~[[F]]~~fixing element according to claim 25, ~~wherein~~ characterised by the fact that the further contact surface on the grommet side is formed by a flange-~~[[like]]~~shaped grommet section projecting over the circumference of the grommet.
27. – 29. (Cancelled)

30. (Currently Amended) The ~~[[F]]~~ fixing element according to claim 17, ~~wherein~~ characterised by the fact that ~~[[the]]~~ a volume of the at least one cavity is at least equal to ~~[[the]]~~ a volume of the at least one projection.